


FISHCABLE®

FISHCABLE®
STAINLESS STEEL
VERY HIGH-EFFICIENCY



7 STRANDS OF 19 WIRES

14+6+1 Use Factory	DIAMETRE mm	KG/100 m	1570 N/mm ²		1770 N/mm ²	
		Weight	MINIMUM BREAKING LOAD			
		Steel Core	Steel Core		Steel Core	
			KN	T	KN	T
 <p>6X19SS</p> <p>Steel core</p> <p>Very high-speed resistance High flexibility ISO 9001 standard</p> <p>Greased Fishcable® H1, Compatible HACCP</p>	3	3.6	-	-	5.29	0.54
	4	6.4	-	-	9.4	0.96
	5	10	-	-	14.7	1.50
	6	14.4	-	-	21.2	2.16
	7	19.6	-	-	28.8	2.94
	8	25.6	33.3	3.40	37.6	3.83
	9	32.4	42.2	4.30	47.6	4.85
	10	40	52.1	5.31	58.8	6.00
	11	48.4	63.1	6.43	71.1	7.25
	12	57.6	75	7.65	84.6	8.63
	13	67.6	88.1	8.98	99.3	10.13
	14	78.4	102	10.40	115	11.73
	16	102.4	133	13.56	150	15.30
	18	129.6	168	17.13	190	19.37
	20	160	208	21.21	230	23.45