


# FISHCABLE®

FISHCABLE®  
ACIER INOX  
TRÈS HAUTE PERFORMANCE



## 6 TORONS DE 19 FILS

14+6+1	DIAMÈTRE	KG/100 m	1570 N/mm <sup>2</sup>		1770 N/mm <sup>2</sup>	
		Poids	RUPTURE MINIMUM			
		Âme Métal	Âme Métal		Âme Métal	
Usage Usine	mm	Âme Métal	KN	T	KN	T
 <p><b>6X19SS</b></p> <p>Âme métallique Résistance à très haute vitesse, Grande flexibilité, Norme iso 9001</p> <p>Graissé Fishcable® H1, Compatible HACCP</p>	3	3.6	-	-	5.29	0.54
	4	6.4	-	-	9.4	0.96
	5	10	-	-	14.7	1.50
	6	14.4	-	-	21.2	2.16
	7	19.6	-	-	28.8	2.94
	8	25.6	33.3	3.40	37.6	3.83
	9	32.4	42.2	4.30	47.6	4.85
	10	40	52.1	5.31	58.8	6.00
	11	48.4	63.1	6.43	71.1	7.25
	12	57.6	75	7.65	84.6	8.63
	13	67.6	88.1	8.98	99.3	10.13
	14	78.4	102	10.40	115	11.73
	16	102.4	133	13.56	150	15.30
	18	129.6	168	17.13	190	19.37
	20	160	208	21.21	230	23.45